

THE SECRET OF SUCCESSFUL POOL

SwimClear™ Mono-élément




Compact design for clear water

- Very fine filtration (20 to 25 microns)
- Ease of maintenance: just one filtration element to clean
- Ease of installation
- NSF (National Sanitation Foundation) Certified
- Excellent hydraulics that reduce installation head losses
- Compact design with minimum ground coverage
- No backwashing: saves on water, heating and chemicals (ideal with a salt chlorinator as there is no loss of salt)
- Can be installed outdoors thanks to its weather-resistant tank






Easy-to-remove filter cartridge



- Ergonomic grip handles: provide multiple handling
- Seasy-lok™ ring design. Quick access to internal components
- 4 Lowest body height to lift elements.
- 5 Complete built-in drain offering full and fast cleaning for simplified filter draining.





SWIMCLEAR™
SINGLE ELEMENT

RE-EQUIPMENT CARTRIDGES SWIMCL FAR™ SINGLE ELEMENT

Effective filtration	Equivalent flow	In/Out	Weight	Dimensions in mm			Item
area	(sand filter)		when empty	Α	В	С	
9.3 m ²	20 m³/h	50/63 mm	15 kg	775	330	464	C100SE
14 m ²	25 m³/h	50/63 mm	16.8 kg	857	330	464	C150SE
18.6 m ²	30 m³/h	50/63 mm	18.1 kg	984	330	464	C200SE

Item	O.D.	I.D.	Height	Quantity required	Item
C100SE	263.9 mm	101.1mm	499.1 mm	1	CX100XRE
C150SE	263.9 mm	101.1mm	591.6 mm	1	CX150XRE
C200SE	263.9 mm	101.1mm	718.6 mm	1	CX200XRE